

- How to use dataframes in Python?
- Import data set as dataframe
- Inspect data frame and access data
- Produce an overview of data features
- Create data plots using matplotlib

Video Tutorials

Pandas Dataframes - Import and Data Handling

Pandas Dataframes - Visualisation


Introduction

This is our first lesson on learning and understanding dataframes in Python.

The diabetes data set is one of the challenging task.

Challenge: The diabetes data set

Here is a screenshot of the so-called diabetes data set. It is taken from this webpage and it is one of the example data sets used to illustrate machine learning functionality in scikit-learn (Part III and Part IV of the course).



AGE	SEX	BMI	BP	S1	S2	S3	S4	S5	S6	Y
59	2	32.1	101	157	93.2	38	4	4.8598	87	151
48	1	21.6	87	183	103.2	70	3	3.8918	69	75
72	2	30.5	93	156	93.6	41	4	4.6728	85	141
24	1	25.3	84	198	131.4	40	5	4.8903	89	206
50	1	23	101	192	125.4	52	4	4.2905	80	135
23	1	22.6	89	139	64.8	61	2	4.1897	68	97
36	2	22	90	160	99.6	50	3	3.9512	82	138
66	2	26.2	114	255	185	56	4.55	4.2485	92	63
60	2	32.1	83	179	119.4	42	4	4.4773	94	110
29	1	30	85	180	93.4	43	4	5.3845	88	310
22	1	18.6	97	114	57.6	46	2	3.9512	83	101
56	2	28	85	184	144.8	32	6	3.5835	77	69
53	1	23.7	92	186	109.2	62	3	4.3041	81	179
50	2	26.2	97	186	105.4	49	4	5.0626	88	185
61	1	24	91	202	115.4	72	3	4.2905	73	118
34	2	24.7	118	254	184.2	39	7	5.037	81	171
47	1	30.3	109	207	100.2	70	3	5.2149	98	166
68	2	27.5	111	214	147	39	5	4.9416	91	144
38	1	25.4	84	162	103	42	4	4.4427	87	97
41	1	24.7	83	187	108.2	60	3	4.5433	78	168
35	1	21.1	82	156	87.8	50	3	4.5109	95	68
25	2	24.3	95	162	98.6	54	3	3.8501	87	49
25	1	26	92	187	120.4	56	3	3.9703	88	68
61	2	32	103.67	210	85.2	35	6	6.107	124	245
31	1	29.7	88	167	103.4	48	4	4.3567	78	184
30	2	25.2	83	178	118.4	34	5	4.852	83	202
19	1	19.2	87	124	54	57	2	4.1744	90	137

This figure captures only the top part of the data. On the webpage you need to scroll down considerably to view the whole content. Thus, to get an **overview** of the dataset is the first main task in Data Science.

The lesson

- introduces code to read and inspect the data
- works with a specific data frame and extracts some techniques to get an overview
- discusses the concept 'distribution' as a way of summarising data in a single figure

To get to know a dataset you need to

- access the data
- check the content
- produce a summary of basic properties

In this lesson we will only look at univariate features where each data column is studied independently of the others. Further properties and bivariate features will be the topic of the next lesson.

Work Through Example

Reading data into a Pandas DataFrame

The small practice data file for this section is called 'everleys_data.csv' and can be downloaded using the link given above in "Materials for this Lesson". To start, please create a subfolder called 'data' in the current directory and put the data file in it. It can now be accessed using the relative path `data/everleys_data.csv` or `data\everleys_data.csv`, respectively.

The file `everleys_data.csv` contains blood concentrations of calcium and sodium ions from 17 patients with Everley's syndrome. The data are taken from a BMJ statistics tutorial. The data are stored as comma-separated values (csv), two values for each patient.

To get to know a dataset, we will use the Pandas package and the Matplotlib plotting. The Pandas package for data science is included in the Anaconda distribution of Python. Check this link for installation instructions to get started.

If you are not using the Anaconda distribution, please refer to these guidelines.

To use the functions contained in Pandas they need to be imported. Our dataset is in 'csv' format, and we therefore need to read it from a csv file. For this, we import the function `read_csv`. This will create a *Pandas dataframe*.

```
1 import sys
2 print(sys.version)
```

```
1 3.10.8 (main, Oct 18 2022, 06:43:21) [GCC 9.4.0]
```

```
1 from pandas import read_csv
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'pandas'
```

Executing this code does not lead to any output on the screen. However, the function is now ready to be used. To use it, we type its name and provide the required arguments. The following code should import the Everley's data into your JupyterLab notebook (or other Python environment):


```
1 # for Mac OSX and Linux
2 # (please go to the next cell if using Windows)
3
4 df = read_csv("data/everleys_data.csv")
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'read_csv' is not defined
```

Data Frames

```
1 # please uncomment for Windows
2 # (please go to previous cell if using Mac OSX or Linux)
3
4 # df = read_csv("data\everleys_data.csv")
```

This code uses the `read_csv` function from Pandas to read data from a data file, in this case a file with extension `'csv'`. Note that the location of the data file is specified within quotes by the relative path to the subfolder `'data'` followed by the file name. Use the JupyterLab file browser to check that subfolder exists and has the file in it.



The screenshot displays the JupyterLab interface. On the left, a file browser shows the directory structure: `/L21_DataFrames / data /`. The files listed are `cervical_cancer.csv`, `diabetes_data.csv`, and `everleys_data.csv`. The `everleys_data.csv` file is selected. On the right, a data preview window titled `everleys_data.csv` shows a table with a delimiter of `,`. The table contains 18 rows of data with columns `calcium` and `sodium`.

	calcium	sodium
1	3.4555817E+00	1.1269098E+02
2	3.6690263E+00	1.2566333E+02
3	2.7899104E+00	1.0582181E+02
4	2.9399E+00	9.8172772E+01
5	5.42606E+00	9.7931489E+01
6	7.1581063E-01	1.2085833E+02
7	5.6523902E+00	1.128715E+02
8	3.5713201E+00	1.1264736E+02
9	4.3000669E+00	1.3203172E+02
10	1.3694191E+00	1.1849901E+02
11	2.550962E+00	1.1737373E+02
12	2.8941294E+00	1.3405239E+02
13	3.6649873E+00	1.0534641E+02
14	1.3627792E+00	1.2335949E+02
15	3.7187978E+00	1.2502106E+02
16	1.8658681E+00	1.1207542E+02
17	3.2728091E+00	1.1758804E+02
18	3.9175915E+00	1.0100987E+02

After execution of the code, the data are contained in a variable called `df`. This is a structure referred to as a Pandas *DataFrame*.

A **Pandas dataframe** is a 2-dimensional labeled data structure with columns of potentially different types. You can think of it as a spreadsheet.

To see the contents of `df`, simply use:

```
1 df
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

(Compare with the result of `print(df)` which displays the contents in a different format.)

The output shows in the first column an index, integers from 0 to 17; and the calcium and sodium concentrations in columns 2 and 3, respectively. The default indexing starts from zero (Python is a 'zero-based' programming language).

In a dataframe, the first column is referred to as *Indices*, the first row is referred to as *Labels*. Note that the row with the labels is excluded from the row count. Similarly, the row with the indices is excluded from the column count.

For large data sets, the function `head` is a convenient way to get a feel of the dataset.

```
1 df.head()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Without any input argument, this displays the first five data lines of the dataframe. You can specify alter the number of rows displayed by including a single integer as argument, e.g. `head(10)`.

If you feel there are too many decimal places in the default view, you can restrict their number by using the `round` function:

```
1 df.head().round(2)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

While we can see how many rows there are in a dataframe when we display the whole data frame and look at the last index, there is a convenient way to obtain the number directly:

```
1 no_rows = len(df)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print('Data frame has', no_rows, 'rows')
```

Data Frames

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'no_rows' is not defined
```

You could see above, that the columns of the dataframe have labels. To see all labels:

```
1 column_labels = df.columns
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print(column_labels)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'column_labels' is not defined
```

Now we can count the labels to obtain the number of columns:

```
1 no_columns = len(column_labels)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'column_labels' is not defined
```

```
1 print('Data frame has', no_columns, 'columns')
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'no_columns' is not defined
```

And if you want to have both the number of the rows and the columns together, use `shape`. `Shape` returns a tuple of two numbers, first the number of rows, then the number of columns.

```
1 df_shape = df.shape
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print('Data frame has', df_shape[0], 'rows and', df_shape[1], 'columns'
      )
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_shape' is not defined
```

Notice that `shape` (like `columns`) is not followed by round parenthesis. It is not a function that can take arguments. Technically, `shape` is a 'property' of the dataframe.

To find out what data type is contained in each of the columns, us `dtypes`, another 'property':

```
1 df.dtypes
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

In this case, both columns contain floating point (decimal) numbers.

DIY1: Read data into a dataframe

Download the data file 'loan_data.csv' using the link given above in "Materials for this Lesson". It contains data that can be used for the assessment of loan applications. Read the data into a DataFrame. It is best to assign it a name other than 'df' (to avoid overwriting the Evereley data set).

Display the first ten rows of the Loan data set to see its contents. It is taken from a tutorial on Data Handling in Python which you might find useful for further practice.

From this exercise we can see that a dataframe can contain different types of data: real numbers (e.g. LoanAmount), integers (ApplicantIncome), categorical data (Gender), and strings (Loan_ID).

```
1 from pandas import read_csv
2
3 # dataframe from .csv file
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'pandas'
```

```
1 df_loan = read_csv("data/loan_data.csv")
2
3 # display contents
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'read_csv' is not defined
```

```
1 df_loan.head(10)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_loan' is not defined
```

Accessing data in a DataFrame

If a datafile is large and you only want to check the format of data in a specific column, you can limit the display to that column. To access data contained in a specific column of a dataframe, we can use a similar convention as in a Python dictionary, treating the column names as 'keys'. E.g. to show all rows in column 'Calcium', use:

Data Frames

```
1 df['calcium']
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

To access individual rows of a column we use two pairs of square brackets:

```
1 df['calcium'][0:3]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Here all rules for slicing can be applied. As for lists and tuples, the indexing of rows is semi-inclusive, lower boundary included, upper boundary excluded. Note that the first pair of square brackets refers to a column and the second pair refers to the rows. This is different from e.g. accessing items in a nested list.

Accessing items in a Pandas dataframe is analogous to accessing the values in a Python dictionary by referring to its keys.

To access non-contiguous elements, we use an additional pair of square brackets (as if for a list within a list):

```
1 df['calcium'][[1, 3, 7]]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Another possibility to index and slice a dataframe is the use of the 'index location' or `iloc` property. It refers first to rows and then to columns by index, all within a single pair of brackets. For example, to get all rows : of the first column (index 0), you use:

```
1 df.iloc[:, 0]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

To display only the first three calcium concentrations, you use slicing, remembering that the upper bound is excluded):

```
1 df.iloc[0:3, 0]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

To access non-consecutive values, we can use a pair of square brackets within the pair of square

brackets:

```
1 df.iloc[[2, 4, 7], 0]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Similarly, we can access the values from multiple columns:

```
1 df.iloc[[2, 4, 7], :]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

To pick only the even rows from the two columns, check this colon notation:

```
1 df.iloc[:18:2, :]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

The number after the second colon indicates the stepsize.

DIY2: Select data from dataframe

Display the calcium and sodium concentrations of all patients except the first. Check the model solution at the bottom for options.

```
1 df[['calcium', 'sodium']][1:]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Mixing the ways to access specific data in a dataframe can be confusing and needs practice.

Search for missing values

Some tables contain missing entries. You can check a dataframe for such missing entries. If no missing entry is found, the function `isnull` will return `False`.

```
1 df.isnull().any()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

This shows that there are no missing entries in our dataframe.

DIY3: Find NaN in dataframe

In the Loan data set, check the entry 'Self-employed' for ID LP001059. It shows how a missing value is represented as 'NaN' (not a number).

Verify that the output of `isnull` in this case is `True`

```
1 df_loan['Self_Employed'][8]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_loan' is not defined
```

```
1 df_loan['Self_Employed'][8:9].isnull()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_loan' is not defined
```

Basic data features

Summary Statistics

To get a summary of basic data features use the function `describe`:

```
1 description = df.describe()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 description
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'description' is not defined
```

The `describe` function produces a new dataframe (here called 'description') that contains the number of samples, the mean, the standard deviation, minimum, 25th, 50th, 75th percentile, and the maximum value for each column of the data. Note that the indices of the rows have now been replaced by strings. To access rows, it is possible to refer to those names using the `loc` property. E.g. to access the mean of the calcium concentrations from the description, each of the following is valid:

```
1 # Option 1
2 description.loc['mean']['calcium']
3
4 # Option 2
```

Data Frames

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'description' is not defined
```

```
1 description.loc['mean'][0]
2
3 # Option 3
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'description' is not defined
```

```
1 description['calcium']['mean']
2
3 # Option 4
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'description' is not defined
```

```
1 description['calcium'][1]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'description' is not defined
```

DIY4: Practice

Use your own .csv data set to practice. (If you don't have a data set at hand, any excel table can be exported as .csv.) Read it into a dataframe, check its header, access individual values or sets of values. Create a statistics using `describe` and check for missing values using `.isnull`.

[ad libitum]

Iterating through the columns

Now we know how to access all data in a dataframe and how to get a summary statistics over each column.

Here is code to iterate through the columns and access the first two concentrations:

```
1 for col in df:
2
3     print(df[col][0:2])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

As a slightly more complex example, we access the median ('50%') of each column in the description and add it to a list:

```
1 conc_medians = list()
2
3 for col in df:
4
5     conc_medians.append(df[col].describe()['50%'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print('The columns are: ', list(df.columns))
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print('The medians are: ', conc_medians)
```

```
1 The medians are: []
```

This approach is useful for data frames with a large number of columns. For instance, it is possible to then create a boxplot or histogram for the means, medians etc. of the dataframe and thus to get an overview of all (comparable) columns.

Selecting a subset based on a template

An analysis of a data set may need to be done on part of the data. This can often be formulated by using a logical condition which specifies the required subset.

For this we will assume that some of the data are labelled '0' and some are labelled '1'. Let us therefore see how to add a new column to our Evereleys data frame which contains the (in this case arbitrary) labels.

First we randomly create as many labels as we have rows in the data frame. We can use the `randint` function which we import from 'numpy.random'. `randint` in its simple form takes two arguments. First the upper bound of the integer needed, where by default it starts from zero. As Python is exclusive on the upper bound, providing '2' will thus yield either '0' or '1' only.

```
1 from numpy.random import randint
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'numpy'
```

```
1 no_rows = len(df)
```

Data Frames

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 randomLabel = randint(2, size=no_rows)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randint' is not defined
```

```
1 print('Number of rows: ', no_rows)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'no_rows' is not defined
```

```
1 print('Number of Labels:', len(randomLabel))
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randomLabel' is not defined
```

```
1 print('Labels:          ', randomLabel)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randomLabel' is not defined
```

Note how we obtain the number of rows (18) using `len` and do not put it directly into the code.

Now we create a new data column in our `df` dataframe which contains the labels. To create a new column, you can simply refer to a column name that does not yet exist and assign values to it. Let us call it 'gender', assuming that '0' represents male and '1' represents female.

As gender specification can include more than two labels, try to create a column with more than two randomly assigned labels e.g. (0, 1, 2).

```
1 df['gender'] = randomLabel
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randomLabel' is not defined
```

```
1 df.head()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Now we can use the information contained in 'gender' to filter the data by gender. To achieve this, we use a conditional statement. Let us check which of the rows are labelled as '1':

```
1 df['gender'] == 1
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

If we assign the result of the conditional statement (Boolean True or False) to a variable, then this variable can act as a template to filter the data. If we call the data frame with that variable, we will only get the rows where the condition was found to be True:

```
1 df_female = df['gender'] == 1
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 df[df_female]
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

Using the Boolean, we only pick the rows that are labelled '1' and thus get a subset of the data according to the label.

DIY5: Using a template

Modify the code to calculate the number of samples labelled 0 and check the number of rows of that subset.

```
1 from numpy.random import randint
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'numpy'
```

```
1 no_rows = len(df)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 randomLabel = randint(2, size=no_rows)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randint' is not defined
```

```
1 df['gender'] = randomLabel
```

Data Frames

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'randomLabel' is not defined
```

```
1 df_male = df['gender'] == 0
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 no_males = len(df[df_male])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df' is not defined
```

```
1 print(no_males, 'samples are labelled "male".')
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'no_males' is not defined
```

Visualisation of data

It is easy to see from the numbers that the concentrations of sodium are much higher than that of calcium. However, to also compare the medians, percentiles and the spread of the data it is better to use visualisation.

The simplest way of visualisation is to use Pandas functionality which offers direct ways of plotting. Here is an example where a boxplot is created for each column:

```
1 import matplotlib.pyplot as plt
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'matplotlib'
```

```
1 df = read_csv("data/everleys_data.csv")
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'read_csv' is not defined
```

```
1 plt.boxplot(df)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'plt' is not defined
```

```
1 plt.show()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'plt' is not defined
```

By default, boxplots are shown for all columns if no further argument is given to the function (empty round parenthesis). As the calcium plot is rather squeezed we may wish to see it individually. This can be done by specifying the calcium column as an argument:

```
1 # Boxplot of calcium results
2 # df.boxplot(column='calcium');
3
4
5 plt.boxplot(df['calcium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'plt' is not defined
```

```
1 plt.show()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'plt' is not defined
```

Plots using Matplotlib

Matplotlib is a comprehensive library for creating static, animated, and interactive visualizations in Python.

The above is an easy way to create boxplots directly on the dataframe. It is based on the library Matplotlib and specifically uses the **pyplot library**. For simplicity, the code is put in a convenient Pandas function.

However, we are going to use **Matplotlib** extensively later on in the course, and we therefore now introduce the direct, generic way of using it.

For this, we import the function `subplots` from the pyplot library:

```
1 from matplotlib.pyplot import subplots
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'matplotlib'
```

The way to use `subplots` is to first set up a figure environment (below it is called 'fig') and an empty coordinate system (below called 'ax'). The plot is then done using one of the many methods available in Matplotlib. We apply it to the coordinate system 'ax'.

As an example, let us create a boxplot of the calcium variable. As an argument of the function we need

to specify the data. We can use the values of the 'calcium' concentrations from the column with that name:

```
1 fig, ax = subplots()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax.boxplot(df['calcium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax.set_title('Boxplot of Everley\'s Calcium');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```




Figure 1: png

Note how following the actual plot we define the title of the plot by referring to the same coordinate system `ax`.

The value of `subplots` becomes apparent when we try to create more than one plot in a single figure.

Data Frames

Here is an example to create two boxplots next to each other. The keyword arguments to use is 'ncols' which is the number of figures per row. 'ncols=2' indicates that you want to have two plots next to each other.

```
1 fig, ax = subplots(ncols=2)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax[0].boxplot(df['calcium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[0].set_title('Calcium')
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].boxplot(df['sodium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].set_title('Sodium');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

Note that you now have to refer to each of the subplots by indexing the coordinate system 'ax'. | This figure gives a good overview of the Everley's data.

If you prefer to have the boxplots of both columns in a single figure, that can also be done:


```
1 fig, ax = subplots(ncols=1, nrows=1)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax.boxplot([df['calcium'], df['sodium']], positions=[1, 2])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax.set_title('Boxplot of Calcium (left) and Sodium (right)')
```

**Figure 2:** png

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

DIY6: Boxplot from Loan data

Plot the boxplots of the 'ApplicantIncome' and the 'CoapplicantIncome' in the Loan data using the above code.

```
1 fig, ax = subplots(ncols=1, nrows=1)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax.boxplot([df_loan['ApplicantIncome'], df_loan['CoapplicantIncome']],
  positions=[1, 2])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax.set_title('Applicant Income (left) & Co-Applicant Income (right)');
```




Figure 3: png

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

Histogram

Another good overview is the histogram: Containers or 'bins' are created over the range of values found within a column and the count of the values for each bin is plotted on the vertical axis.

```
1 fig, ax = subplots(ncols=2, nrows=1)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax[0].hist(df['calcium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[0].set(xlabel='Calcium', ylabel='Count');
```




Figure 4: Applicant Income (left) & Co-Applicant Income (right)

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].hist(df['sodium'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].set(xlabel='Sodium', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 fig.suptitle('Histograms of Everley concentrations', fontsize=15);
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'fig' is not defined
```

This also shows how to add labels to the axes and a title to the overall figure.

This uses the default value for the generation of the bins. It is set to 10 bins over the range of which values are found. The number of bins in the histogram can be changed using the keyword argument 'bins':




Figure 5: png

Data Frames

```
1 fig, ax = subplots(ncols=2, nrows=1)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax[0].hist(df['calcium'], bins=5)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[0].set(xlabel='Calcium, 5 bins', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].hist(df['calcium'], bins=15)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[1].set(xlabel='Calcium, 15 bins', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 fig.suptitle('Histograms with Different Binnings', fontsize=16);
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'fig' is not defined
```

Note how the y-label of the right figure is not placed well. To correct for the placement of the labels and the title, you can use `tight_layout` on the figure:

```
1 fig, ax = subplots(ncols=2, nrows=1)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax[0].hist(df['calcium'], bins=5)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax[0].set(xlabel='Calcium, 5 bins', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
```




Figure 6: png

Data Frames

```
name 'ax' is not defined
```

```
1 ax[1].hist(df['calcium'], bins=15)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'ax' is not defined
```

```
1 ax[1].set(xlabel='Calcium, 15 bins', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'ax' is not defined
```

```
1 fig.suptitle('Histograms with Different Binnings', fontsize=16);
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'fig' is not defined
```

```
1 fig.tight_layout()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'fig' is not defined
```




Figure 7: png

DIY7: Create the histogram of a column

Take the loan data and display the histogram of the loan amount that people asked for. (Loan amounts are divided by 1000, i.e. in k£ on the horizontal axis). Use e.g. 20 bins.

```
1 # Histogram of loan amounts in k£
2
3 fig, ax = subplots()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 ax.hist(df_loan['LoanAmount'], bins=20)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax.set(xlabel='Loan amount', ylabel='Count');
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

```
1 ax.set_title('Histograms of Loan Amounts', fontsize=16);
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```

Handling the Diabetes Data Set

We now return to the data set that started our enquiry into the handling of data in a dataframe.

We will now:

- Import the diabetes data from 'sklearn'
- Check the shape of the dataframe and search for NaNs
- Get a summary plot of one of its statistical quantities (e.g. mean) for all columns

First we import the data set and check its `head`. Wait until the numbers show below the code, it might take a while.

```
1 from sklearn import datasets
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):
  ModuleNotFoundError: No module named 'sklearn'
```




Figure 8: Histograms of Loan Amounts

```
1 diabetes = datasets.load_diabetes()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'datasets' is not defined
```

```
1 X = diabetes.data
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'diabetes' is not defined
```

```
1 from pandas import DataFrame
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords):  
  ModuleNotFoundError: No module named 'pandas'
```

```
1 df_diabetes = DataFrame(data=X)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:  
  name 'DataFrame' is not defined
```

```
1 df_diabetes.head()
```

Data Frames

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_diabetes' is not defined
```

If you don't see all columns, use the cursor to scroll to the right.

Now let's check the number of columns and rows.

```
1 no_rows = len(df_diabetes)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_diabetes' is not defined
```

```
1 no_cols = len(df_diabetes.columns)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_diabetes' is not defined
```

```
1 print('Rows:', no_rows, 'Columns:', no_cols)
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'no_rows' is not defined
```

There are 442 rows organised in 10 columns.

To get an overview, let us extract the mean of each column using 'describe' and plot all means as a bar chart. The Matplotlib function to plot a bar chart is `bar`:

```
1 conc_means = list()
2
3 for col in df_diabetes:
4     conc_means.append(df_diabetes[col].describe()['mean'])
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_diabetes' is not defined
```

```
1 print('The columns are: ', list(df_diabetes.columns))
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'df_diabetes' is not defined
```

```
1 print('The medians are: ', conc_means, 2)
```

```
1 The medians are: [] 2
```

```
1 fig, ax = subplots()
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'subplots' is not defined
```

```
1 bins = range(10)
2
3 ax.bar(bins, conc_means);
```

```
1 Error in py_call_impl(callable, dots$args, dots$keywords): NameError:
  name 'ax' is not defined
```




Figure 9: png

The bars in this plot go up and down. Note, however, that the vertical axis has values ranging from $-10^{(-15)}$ to $+10^{(-15)}$. This means that for all practical purposes all means are zero. This is not a coincidence. The original values have been normalised to zero mean for the purpose of applying some machine learning algorithm to them.

In this example, we see how important it is to check the data before working with them.

Assignment: The cervical cancer data set

Download the cervical cancer data set provided, import it using `read_csv`.

- How many rows and columns are there?

- How many columns contain floating point numbers (float64)?
- How many of the subjects are smokers?
- Calculate the percentage of smokers
- Plot the age distribution (with e.g. 50 bins)
- Get the mean and standard distribution of age of first sexual intercourse

Keypoints

- learned importing data set as dataframe
- learned inspecting data frame and accessing data
- Producing an overview of data features
- Creating data plots using matplotlib

Download the pdf

This section's pdf can be accessed at:[Download pdf](#)

Download jupyter notebook

This section's material in jupyter notebook can be accessed at:[Download notebook \(ipynb\)](#)